



Tech Info Library

Macintosh Performa 6360/160: Specifications (11/96)

Article Created: 25 September 1996

Article Reviewed/Updated: 12 November 1996

TOPIC -----

This article contains the technical specifications for the Macintosh Performa 6360/160 computer.

DISCUSSION -----

Microprocessor

=====

- * PowerPC 603e processor running at 160 MHz
- * Integrated floating-point unit
- * 40-MHz, 64-bit bus
- * Optional High Performance Module (256K level 2 cache; see ordering information)
- * 32K internal cache

Memory

=====

- * Two DIMM expansion slots
- * Comes with 16 MB of RAM (8 MB on logic board and 8 MB in one DIMM socket)
- * Can be expanded to 136 MB
- * Uses 64-bit-wide, 168-pin, noncomposite, 70-nanosecond or faster DIMMs (1K or 2K refresh)

Disk drives

=====

- * Internal 1.2GB IDE hard disk drive
- * Internal Apple SuperDrive floppy disk drive
 - Uses high-density, 1.4MB floppy disks
 - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- * Internal 8x-speed CD-ROM drive

Modem

=====

- * 28.8-Kbit/s internal Geoport data/voice/fax modem (fax speeds up to 14.4 Kbit/s; data speeds up to 28.8 Kbit/s)
- * Built-in error correction and compression (MNP4, V.42, MNP5, V.42bis)

Sound

=====

- * Stereo 16-bit sound
- * SRS surround sound enhancement
- * Sound-input port (for an Apple PlainTalk microphone)
- * Sound-output port
- * Front headphone jack and volume control

Display support

=====

- * 1 MB of video RAM
- * 16-bit color for display of up to 32,768 colors on monitors using 640- by 480-pixel or 800- by 600-pixel resolution
- * 8-bit color for display of 256 colors on monitors using 832- by 624-pixel or 1,024- by 768-pixel resolution

Interfaces

=====

- * PCI expansion slot (requires PCI card that comes with a Macintosh driver and is PCI 2.0 compliant; a NuBus card cannot be used in this slot)
- * PCI-based communications (Comm II) slot for a 28.8-Kbit/s modem (used by the built-in data/voice/fax modem)
- * Two serial ports (RS-232/RS-422) for an AppleTalk network connection, other network connections, communications equipment (including GeoPort compatible devices), or a printer (one port used by the built-in modem)
- * SCSI interface port for connecting as many as six external SCSI devices, such as disk drives, CD-ROM drives, and scanners (multiple devices can be connected to each other from one port)
- * Apple Desktop Bus port for mouse, keyboard, and other devices (multiple devices can be connected to each other from one port)
- * Video-output port
- * Video-input slot for optional Apple Video System (supports NTSC, PAL, and SECAM video formats)
- * Expansion bay for optional Apple TV/FM Radio System
- * Infrared receiver for remote control (provided with Apple TV/FM Radio System and certain other accessories)

Disability access

=====

- * CloseView software magnifies screen image up to 16 times
- * Easy Access software permits combination keys to be pressed sequentially and enables cursor control from the numeric keypad instead of the mouse
- * "Visual beep" replaces audible system alerts

Electrical requirements and compliance

=====

- * Line voltage: 90 to 270 V AC, RMS, single phase
- * Frequency: 47 to 63 Hz
- * Power: 150 W maximum (continuous)
- * Includes low-power sleep mode
- * U.S. EPA Energy Star compliant

Size and weight

=====

- * Height: 4.3 in. (11.0 cm)
- * Width: 12.6 in. (32.0 cm)
- * Depth: 16.5 in. (42.0 cm)
- * Weight: 17 lb. (7.7 kg)

Operating environment

=====

- * Operating temperature: 50 to 104 degrees F (10 to 40 degrees C)
- * Storage temperature: -40 to 116.6 degrees F (-40 to 47 degrees C)
- * Relative humidity: 5% to 95%, noncondensing
- * Maximum altitude: 10,000 ft. (3,048 m)

Article Change History:

- 12 Nov 1996 - Clarified number of DIMM slots.
- 11 Nov 1996 - Clarified modem type.
- 21 Oct 1996 - Changed distribution status.

Copyright 1996, Apple Computer, Inc.

Keywords: kppc,specsht

=====

This information is from the Apple Technical Information Library.

19961113 08:31:20.00

Tech Info Library Article Number: 20461