



Tech Info Library

Apple Hard Disk 20SC: Specifications (Discontinued)

Article Created: 1 October 1986

Article Reviewed/Updated: 10 September 1987.

I. Technical Specifications

A. Storage:

1. Formatted data capacity: 20 megabytes
2. Data surfaces: 4
3. Heads per surface: 1
4. Block size: 512 bytes
5. Total disk blocks: 39,360
6. Sectors per track: 32

B. Drive:

- Winchester technology
- 1. Average access time: 65 to 85 milliseconds
- 2. Data transfer rate: up to 1.25 megabytes per second
- 3. Rotation speed: 2,744 RPM
- 4. Startup: 9 seconds
- 5. Spindown: 20 seconds

C. Interfaces

- Two 50-pin connectors
 - One expansion port, a "pass-thru" SCSI port, allows for connection of second HD20 or backup device

D. Electrical

-- Automatically adapting to supply

1. Line voltage: 85 to 270 volts AC, RMS

2. Frequency: 47 to 64 Hz

3. Power consumption: 60 watts

E. Environmental

1. Temperature:

	Degrees	
	Celsius	Fahrenheit
a. Operating:	10 to 40	50 to 104
b. Storing:	-40 to 50	-40 to 122

2. Relative humidity: 20 to 80 percent (noncondensing)

3. Altitude:

	feet	meters
a. Operating:	-1000 to 10,000	-305 to 3,050
b. Nonoperating (shipping):	-1000 to 40,000	

F. Physical

	mm	inches
1. Height:	78	3.1
2. Width:	246	9.7
3. Depth:	266	10.5
4. Maximum weight:	3.63kg or 8 pounds	

II. System Configuration

A. Cable: Apple SCSI System Cable

B. Connector:

1. SCSI port of Macintosh Plus, Macintosh SE, Macintosh II

2. SCSI connector of Apple II SCSI Card for:

- a. Apple IIGS
- b. Apple IIe
- c. Apple II Plus

Copyright 1990 Apple Computer, Inc.

Keywords: SPECSHT

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 1931