



Tech Info Library

LaserWriter IISC: Specifications (Discontinued)

Article Created: 15 March 1991

Marking Engine

Canon LBP-SX laser xerographic

Processor

Motorola 68000 (7.45 MHz clock speed)

Memory

16K ROM; 1MB RAM

Interfaces

SCSI and Apple Desktop Bus (for future expansion) ports

Macintosh Fonts (on Disk)

Times, Helvetica, Courier, and Symbol typefaces in 9-, 10-, 12-, 14-, 18-, and 24-point sizes. (For best results, these fonts should be installed in the System file of your Macintosh computer from the disks shipped with the LaserWriter IISC)

Speed

8 pages per minute maximum throughput (actual speed depends on images printed)

Print Quality

All text and graphics printed at 300 by 300 dots per inch, full page

Print Materials

Letter, legal, A4, and B5 sizes using 16- to 20-lb. single-sheet photocopy bond, 8- to 34-lb. letterhead and colored stock, or transparency overhead film. Envelopes, labels, and paper (up to 36-lb.) supported via manual feed. Envelopes also supported via optional envelope tray.

Print Capacities

-
- Paper cassettes hold 200 sheets of 20-lb. paper.
 - Envelope cassette holds 15 envelopes.

Printable Surface

- letter size: 8.0 by 10.5 in.
 - legal: 8.0 by 13.0 in.
 - A4: 7.41 by 10.86 in.
 - B5: 7.69 by 10.16 in.
- (Actual printable area may vary depending on application.)

Size and Weight

- Height: 8.6 in. (21.8 cm)
- Width: 20 in. (50.8 cm)
- Width: With letter tray attached, 26.4 in. (67.1 cm)
- Depth: 18.5 in. (47 cm)
- Weight: 45 lb. (20.25 kg)

Operating Environment

- Temperature: 50 to 90 degrees F (10 to 32 C)
- Humidity: 20% to 80%

Power Requirements

90 to 126 VAC, 50 to 60 Hz
Copyright 1991, Apple Computer, Inc.

Keywords: SPECSHT

=====
This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 6970