



Tech Info Library

Apple Scribe Printer: Configuration Table

System	SW-1 12345678	Cable Required

Apple III	11010000	A+B
Macintosh	11010000	C
Lisa	11010000	A+B
Apple IIc	11010000	E *
Super Serial	11010000	B
High Speed Serial	N/A	N/A

Key: 0 = off = open; 1 = on = closed
* - Using default port settings

Cables:	Letter	Part Number	Comments
	A	590-0029-00	Modem Eliminator
	B	590-0037-B	DB-25 to DB-25
	C	590-0169	DB-9 to DB 25
	E	590-0191-A	5-pin DIN to DB-25

Apple III Driver Configuration:

Driver Data Configuration Block

	0	1	2	3	4	5	6	7	8	9	A	B
RS-232	0E	00	10	10	10	00	13	11	DF	84	50	80
Printer	0E	00	10	10	10							

Super Serial Card Configuration:

	1	2	3	4	5	6	7
SW1	Off	Off	Off	On	Off	On	On
SW2	On	On	Off	Off	On	Off	Off

The jumper block should be pointing towards terminal.
The Apple Interface Manual, Apple Computer (UK) Ltd.

Keywords: <None>

=====

This information is from the Apple Technical Information Library.

19960215 11:05:19.00

Tech Info Library Article Number: 1058